

IW24 UNDERWATER IMPACT WRENCH

STANLEY



SPECIFICATIONS

Capacity	1½" Square Drive
Torque	800 -3500 ft lbs / 1088-4760 Nm
Flow Range	7-12 gpm / 26-45 lpm
Working Pressure	1800-2000 psi / 124-140 bar
Full Relief Setting	2250 psi / 155 bar
Weight	43 lbs / 19½ kg
Length	16½" / 41 cm
Width	5.1" / 13 cm
Hydraulic Ports	-8 SAE O-ring
Connect Size and Type	¾" Male Pipe Adapter
Couplers	No (See Accessories)
Hose Whips	No (See Accessories)

FEATURES

- Integral Stanley Hyrevz gear motor produces high torque
- Stainless Steel spools and fasteners
- Forward-Reverse with variable speed
- "D" style grip handle with inside trigger
- Feathering on/off trigger for precise control
- Adjustable impact intensity
- 3500 ft lbs/4760 Nm of maximum impact torque
- Durable swing hammer mechanism
- Cast-in lifting eye



The Stanley **IW24** is an extreme duty 1½" square drive impact wrench designed for the toughest underwater bolting applications. Powered by a Stanley integral Hyrevz motor, the **IW24** has a durable swing hammer impact mechanism with adjustable impact intensity from 800 to 3500 ft lbs (1088 to 4760 Nm) of torque. Designed to run from a wide range of hydraulic circuits, this wrench allows underwater bolting with the best in the most extreme applications. "D" style grip handle with side assist handle and hi-visibility yellow paint is standard.

IW24 UNDERWATER IMPACT WRENCH

STANLEY

ORDERING INFORMATION

PART NUMBER

IW24360 Impact Wrench, Underwater, 1½" Square Drive, less couplers

ACCESSORIES

03971 Flush-Face Coupling Set, ¾" NPT

03974 Flush-Face Coupling Set, ½" NPT

06830 Hose Whip 18" long, -8 SAE x 1/2" NPT

31848 Dual Hose, 50' x ½", with couplers

31972 Dual Hose, 25' x ½", with couplers

58633 Twinned Hose, 25' x ½", with couplers

58634 Twinned Hose, 50' x ½", with couplers

When hydraulic hose exceeds 100' (30.4 m) in length, increase I.D. of both pressure and return hose. For more information, consult Stanley Hydraulic Tools.

IMPORTANT

To fill out a Product Warranty Recording form and for information on your warranty visit stanleyhydraulic.com and select the Warranty tab.



Note: The warranty recording form must be submitted to validate the warranty.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specifications and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.